

Product data sheet

Specifications



APC Netshelter Rack Automatic Transfer Switch, 2U, 32A, 230V, 2 IEC 309 IN, 16 C13, 2 C19 OUT, 50/60 Hz

AP4424A

Overview

Lead time Usually in Stock

Main

| | |
|---------------------------|---|
| Main Input Voltage | 230 V AC 1 phase |
| Product or Component Type | Automatic transfer switch |
| Main Output Voltage | 230 V AC 1 phase |
| Input Connection Type | IEC 60320 IEC 60309 32 A 2P+E IEC 60320 |
| number of rack unit | 2U |
| Cable length | 8 ft (2.4 m) |
| Number of cables | 2 |
| Provided Equipment | Mounting Hardware Rack Mounting brackets |

Physical

| | |
|---------------------|------------------------|
| Color | Black |
| Height | 3.5 in (8.8 cm) |
| Width | 17.008 in (43.2 cm) |
| Depth | 9.3 in (23.6 cm) |
| Net Weight | 15.30 lb(US) (6.94 kg) |
| mounting location | Front Rear |
| Mounting preference | No preference |
| Mounting Mode | Rack-mounted |
| mounting position | Horizontal |

Input

| | |
|--------------------------|-------------|
| Input Frequency | 50/60 Hz |
| Acceptable Input Voltage | 207...253 V |
| Load Capacity | 7400 VA |

Output

| | |
|--------------------------------------|------|
| Maximum Total Current Draw per Phase | 32 A |
| Number of power socket outlets | 18 |

| | |
|-----------------|-----------------|
| Protection Type | Circuit breaker |
|-----------------|-----------------|

Conformance

| | |
|------------------------|---|
| Product Certifications | EN 55022 class A FCC part 15 class A |
|------------------------|---|

| | |
|-----------|---|
| Standards | EN 55022 Class A FCC Part 15 class A |
|-----------|---|

Environmental

| | |
|---------------------------------------|--|
| Ambient Air Temperature for Operation | 23.0000000000...113.0000000000 °F (-5...45 °C) |
|---------------------------------------|--|

| | |
|-------------------|----------|
| Relative Humidity | 5...95 % |
|-------------------|----------|

| | |
|--------------------|--------------|
| Operating altitude | 0...10000 ft |
|--------------------|--------------|

| | |
|-------------------------------------|--|
| Ambient Air Temperature for Storage | -13.0000000000...149.0000000000 °F (-25...65 °C) |
|-------------------------------------|--|

| | |
|---------------------------|----------|
| Storage Relative Humidity | 5...95 % |
|---------------------------|----------|

Ordering and shipping details

| | |
|------|--------------|
| GTIN | 731304432456 |
|------|--------------|

Packing Units

| | |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

| | |
|------------------------------|---|
| Number of Units in Package 1 | 1 |
|------------------------------|---|

| | |
|------------------|----------------|
| Package 1 Height | 8.3 in (21 cm) |
|------------------|----------------|

| | |
|-----------------|-------------------|
| Package 1 Width | 23.0 in (58.4 cm) |
|-----------------|-------------------|

| | |
|------------------|--------------------|
| Package 1 Length | 14.02 in (35.6 cm) |
|------------------|--------------------|

| | |
|------------------|------------------------|
| Package 1 Weight | 20.79 lb(US) (9.43 kg) |
|------------------|------------------------|

| | |
|------------------------|-----|
| Unit Type of Package 2 | PAM |
|------------------------|-----|

| | |
|------------------------------|----|
| Number of Units in Package 2 | 20 |
|------------------------------|----|

| | |
|------------------|------------------|
| Package 2 Height | 47.2 in (120 cm) |
|------------------|------------------|

| | |
|-----------------|------------------|
| Package 2 Width | 39.4 in (100 cm) |
|-----------------|------------------|

| | |
|------------------|------------------|
| Package 2 Length | 47.2 in (120 cm) |
|------------------|------------------|

| | |
|------------------|-------------------------|
| Package 2 Weight | 443.6 lb(US) (201.2 kg) |
|------------------|-------------------------|

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Take-back Transparency RoHS/REACH

Resource performance

Take-Back Program Available

Well-being performance

Toxic Heavy Metal Free

Lead Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)

California Proposition 65 WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
