Product datasheet

Specifications





Rack PDU, Basic, Zero U, 32A, 230V, (20)C13 & (4)C19

AP7553

Overview

Lead time

Usually in Stock

Main

mann	
Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	3.05 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit

Complementary

Input Voltage	200 V
	208 V
	230 V
	200 .
Height	161.9 cm
Width	5.6 cm
Output Voltage	230 V
Depth	4.4 cm
Net weight	5.57 kg
mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
mounting mode	Rack-mounted
Rack units	0U
mounting position	Vertical
Input current limits	32 A
Load capacity	7400 VA
Network frequency	4763 Hz
Outlet type and quantity	20 IEC 60320 C13
	4 IEC 60320 C19

Environment



Product certifications	CE VDE
Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

-	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	212.1 cm
Package 1 Width	15.2 cm
Package 1 Length	12.7 cm
Package 1 Weight	6.466 kg

Contractual warranty

Warranty

2 years repair or replace



Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.



Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Lead Free

Certifications & Standards

Eu Rohs Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information



