# Eaton 9E3000I

# Catalog Number: 9E3000I

Eaton 9E UPS, 3000 VA, 2400W, Input: C20, Output: (6) C13, (1) C19, Tower

# General specifications

Product Name

Eaton 9E UPS

UPC

786689166588

**Product Height** 

33 cm

**Product Weight** 

24.2 kg

Certifications

IEC/EN 62040-1

IEC/EN 62040-2

CE

EAC

Catalog Number

9E3000I

Product Length/Depth

19 cm


**Product Width** 

39.9 cm

Compliances

CE Marked

TUV





# Battery

Battery type

Sealed, lead-acid

Runtime graph

View runtime graph

Battery replacement

Replacable batteries

**Battery quantity** 

6

Battery management

Automatic battery test

Deep discharge protection

Battery rating

12 V / 9 Ah

Extended battery capability

Yes

#### Electrical output

Receptacle

(6) C13, (1) C19

Voltage

230V

Wattage

2400 W

Output power factor

8.0

Output voltage range

220/230/240 V +/- 2%

Output waveform

Sine wave

Output nominal voltage

230V default (220/230/240V)

Voltage distortion output (linear load) - max

3

Feed type

1

**Topology** 

Online/Double-conversion

VA rating

3000 VA

## Electrical input

Input connection

C20

Input nominal voltage

230V default (220/230/240V)

Nominal frequency

50/60 Hz

Input power factor

>.99

Input voltage range

176-300 V (100 V-300 V with derating)

#### Communications

Includes network card

No

Communication

USB port (HID compliant)

Serial port (RS232)

Communication slot

Ethernet interface

No

User interface

LCD Display

#### Input frequency range

40-70 Hz

#### Potential free switch contact

No

#### **Expansion slots**

One slot for optional communication card

#### Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power

Protector

#### Type of interface

Other

#### Environmental

#### Altitude

3000 m

#### Noise level

<37 dB at 1 meter

#### Temperature range

0° to 40°C (32° to 104°F)

#### Relative humidity

0-95% non-condensing

# Additional specifications

#### Construction type

Free standing model

#### Package contents

**UPS** 

USB cable

Serial cable

Quickstart guide

Safety instructions

### Phase (output)

1

## Internal bypass

Yes

#### Auto shutdown function

Yes

#### Color

Black

#### Efficiency

91

#### Rack mounting kit

No

#### Phase (input)

1

# Hot swap power

No

## Resources

Compliance information

EU declaration of conformity Eaton 9E UPS

Declarations of conformity

EU Declaration of Conformity

Manuals and user guides

Eaton 9E 1kVA-3kVA UPS Eaton 9E EBM - Advance user guide

Technical data sheets

Eaton 9E UPS - Datasheet



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia