

# Product datasheet

Specifications



APC Easy Rack PDU, Metered, 0U,  
1 Phase, 7.4kW, 230V, 32A, 20 x  
C13 and 4 x C19 outlets, IEC60309  
2P+E inlet

EPDU1132M

## Overview

Lead time Usually in Stock

## Main

Colour	Black
Product or component type	PDU
PDU type	Metered
Cord length	3.00 m
Number of cables	1
Provided equipment	Installation guide Toolless mounting kit User manual Vertical mounting brackets

## Complementary

Input Voltage	200 V 208 V 230 V
Height	117.5 cm
Width	6.2 cm
Output Voltage	230 V
Depth	4.44 cm
Product weight	3.72 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
permissible voltage	220...240 V
Max line current	32 A
Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

---

Outlet type and quantity	20 IEC 60320 C13 4 IEC 60320 C19
--------------------------	-------------------------------------

## Environment

---

Product certifications	CE TÜV EAC RCM
------------------------	-------------------------

---

Ambient air temperature for operation	-5...45 °C
---------------------------------------	------------

---

Relative humidity	5...95 %
-------------------	----------

---

Operating altitude	0...10000 ft
--------------------	--------------

---

Ambient air temperature for storage	-25...65 °C
-------------------------------------	-------------

---

Storage Relative Humidity	5...95 %
---------------------------	----------

---

Storage altitude	0.0000000000...15240.0000000000 m
------------------	-----------------------------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	132 cm
------------------	--------

---

Package 1 Width	11 cm
-----------------	-------

---

Package 1 Length	16 cm
------------------	-------

---

Package 1 Weight	4.48 kg
------------------	---------

## Contractual warranty

---

Warranty	1 year repair or replace
----------	--------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **28890**

Environmental Disclosure [Product Environmental Profile](#)

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

SCIP Number **780cb2d6-f852-4c3c-987f-e705629194ca**

China RoHS Regulation [China RoHS declaration](#)

### Use Again

#### Repack and remanufacture

Circularity Profile [End of Life Information](#)

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back **No**