## **Specifications**

Photo is representative

## Eaton EFLX6B

Eaton FlexPDU, 1U, C20 input, 4 kW, 16A, 200-240V, Outlets: (1) C19/(6) BS

General specifications	
PRODUCT NAME	Eaton Flex Rack PDU
CATALOG NUMBER	EFLX6B
EAN	3553340684265
PRODUCT LENGTH/DEPTH	120 mm
PRODUCT HEIGHT	52 mm
PRODUCT WIDTH	483 mm
PRODUCT WEIGHT	1.6 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	CE
MODEL CODE	EATON FLEXPDU 6 BS



Additional specifications		
FORM FACTOR	1U	
OUTLET CONTROL	No	

• Rack PDU Mounting accessories

Quickstart guide

• Safety Instructions

**OPERATING** 0° to 60°C (32° to 140°F) TEMPERATURE

Physical	
MOUNTING DIRECTION	Horizontal
COLOR	Black

**Electrical input** 

PACKAGE CONTENTS

**Communications** 

INPUT CONNECTION	C20
WATTAGE	3.84 kW max
AMPERAGE RATING	16A
INPUT VOLTAGE	200-240V
FREQUENCY RATING	50/60 Hz
CORD LENGTH	2m
PHASE	Single-phase

ETHERNET INTERFACE	No
MASS CONFIGURATION	No
SNMP	No
SERIAL INTERFACE	No

Additional specifications	
ELECTRICAL CONNECTION	Socket outlet
MOUNTING DIMENSION (METRICAL)	52
OVER VOLTAGE CATEGORY	2
MOUNTING DIMENSION (STANDARDIZED)	482.6 mm (19 inch)
SWITCHABLE	No

Resources	
APPLICATION NOTES	Eaton network closet solutions brochure
BROCHURES	Eaton FlexPDU and Eaton HotSwap MBP - Datasheet
	Eaton ePDU G3 - Brochure
	Eaton UPS and battery services - EN
	Eaton Flex and Hotswap MBP ePDU brochure
	Eaton UPS Services Quick Guide - EN
COMPLIANCE INFORMATION	EU declaration of conformity Eaton FlexPDU and Eaton Hot- Swap MBP
MANUALS AND USER GUIDES	Eaton Flex PDU - Installation and user manual (multiple languages)
	Eaton FlexPDUs and HotSwap MBP installation and user manual
WHITE PAPERS	Quick guide to power distribution

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



**Eaton Corporation plc** 

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

All other trademarks are property of their respective owners.







